



M3V, M5V,
M3V-UK, M5V-US



M3T, M3TV,
M5T, M5TV



M3XV, M5XV



M6, M6X

ODP (Open Drip Proof), Splashproof, IP24 Variable Speed Motors

Model	Certification	Requirements	Input/Output (W)	RPM	Maximum Viscosity
M3V	QPS	115V/50-60Hz	650/400	3,500-10,000	500 cP
M5V	CE	230V/50-60Hz	650/400	3,500-10,000	500 cP
M5V-US	CE	230V/50-60Hz	650/400	3,500-10,000	500 cP
M3V-UK	CE	115V/50-60Hz	650/400	3,500-10,000	500 cP

*Suitable for 230V, 60 Hz. Includes NEMA 6-15 plug

TEFC (Totally Enclosed Fan Cooled) IP55 Motors

Model	Certification	Requirements	Input/Output (W)	RPM	Maximum Viscosity
M3T	QPS	115V/60Hz	1000/680	12,000	1,000 cP
M5T	CE	230V/50-60Hz	1000/680	12,000	1,000 cP
M3TV	QPS	115V/60Hz	1000/680	0-12,000**	2,000 cP
M5TV	CE	230V/50-60Hz	1000/680	0-12,000**	2,000 cP

**Variable speed

Explosion Proof Motors

Model	Certification	Requirements	Input/Output (W)	RPM	Maximum Viscosity
M3XV	QPS	115V/60Hz	1000/680	0-12,000**	2,000 cP
M5XV [†]	CE	230V/50-60Hz	1000/680	0-12,000**	2,000 cP

**Variable speed

[†]ATEX certified option available. Contact factory for more information.

Air Motors*

Model	Certification	Requirements	Input/Output (W)	RPM	Maximum Viscosity
M6 [†]	CE	80-100psi@15-32cfm	400	300-9,000	330 cP
M6X [†]	CE	80-100psi@15-32cfm	600	300-6,000	330 cP

*An air motor is a non-electrical device meaning possibility of explosion from igniting flammables is reduced.

[†]ATEX certified option available. Contact factory for more information