



M3V, M5V,
M3V-UK, M5V-US

M3T, M3TV,
M5T, M5TV

M3XV, M5XV

M6, M6X

ODP (Open Drip Proof), Splashproof, IP24 Variable Speed Motors

Model	Certification	Requirements	Input/Output (W)	RPM	Maximum Viscosity
M3V	QPS	115V/50-60Hz	650/400	3,500-10,000	200 cP
M5V	CE	230V/50-60Hz	650/400	3,500-10,000	200 cP
M5V-US	CE	230V/50-60Hz	650/400	3,500-10,000	200 cP
M3V-UK	CE	115V/50-60Hz	650/400	3,500-10,000	200 cP

*Suitable for 230V, 60 Hz. Includes NEMA 6-15 plug

TEFC (Totally Enclosed Fan Cooled) IP55 Motors

Model	Certification	Requirements	Input/Output (W)	RPM	Maximum Viscosity
M3T	QPS	115V/60Hz	1000/680	12,000	200 cP
M5T	CE	230V/50-60Hz	1000/680	12,000	200 cP
M3TV	QPS	115V/60Hz	1000/680	0-12,000**	200 cP
M5TV	CE	230V/50-60Hz	1000/680	0-12,000**	200 cP

**Variable speed

Explosion Proof Motors

Model	Certification	Requirements	Input/Output (W)	RPM	Maximum Viscosity
M3XV	QPS	115V/60Hz	1000/680	0-12,000**	200 cP
M5XV	CE	230V/50-60Hz	1000/680	0-12,000**	200 cP

**Variable speed

Air Motors*

Model	Certification	Requirements	Input/Output (W)	RPM	Maximum Viscosity
M6	CE	80-100psi@15-32cfm	400	300-9,000	200 cP
M6X	CE	80-100psi@15-32cfm	600	300-6,000	200 cP

*An air motor is a non-electrical device meaning possibility of explosion from igniting flammables is reduced.